

**TELEPHONY PRODUCTS**

**GX-500  
REMOTE MIXER**

The GX-500 is one of the most versatile remote mixers on the market. It has all of the features that you would find in much larger mixers or consoles. The unit comes with a plastic protective case, long life rechargeable batteries, and is capable of 2 telephone connections. It can be run on either battery or AC and has 4 mic input channels and 2 auxiliary inputs. The GX-500 is loaded with all the features that make remote broadcasting easier than ever.



**GX-500 Features**

- 4 mic channels and 2 auxiliary inputs.
- 4 headphone jacks.
- Peak limiter.
- Squelch/mute switch.
- Internal tone generator.
- Radio monitor input.
- Tone/pulse dialing and electronic ringer.
- Rechargeable batteries for up to 10 hours of use.
- Second phone line capability.
- Aux. output - line or mic level.
- External AC supply.
- Plastic carrying case included.

**GX-500 Specifications**

**Dimensions:** 1.5"H x 9.4"W x 6.1"D (3.17 cm x 23.88 cm x 15.49 cm).  
**Boxed Dimensions:** 17"H x 13"W x 9"D (43.18 cm x 33.02 cm x 22.86 cm).  
**Weight/unit:** Net 3 lbs. Shipping 7 lbs.

**ANALOG CELLCAST**

- Magnetic mount antenna included as shown.
- 3.2dB gain.
- 12' foot cable.
- (Part #540-129.)



Cellcast® is another quality remote broadcast product available from MARTI. This remote broadcasting studio eliminates line-of-sight requirements, phone line access, and antenna problems while reporting from the scene because the Cellcast is CELLULAR and battery operated — JUST TURN IT ON and GO...

\*Not for use on Digital Cellular Networks.


**Cellcast Features**

- Cellular or land line analog transmission.
- 3 power options: A/C power, battery or 12V(cigarette lighter) adapter.
- 2 line, 16 segment back-lit LCD display
- 3 watt analog cellular transceiver.
- RJ11C - 6 pin land line connector.
- 4 channel mixer, program or cue, mic or line selectable.
- Software selectable single line encoder (compatible with any major single line decoder) for improved audio frequency response.
- 600 ohm output.
- Low battery indicator (audible alarm can only be heard by the operator).
- Lock function for all audio settings (software security code).
- Pulse or tone dial.
- Pre-programmable cellular telephone number and functions.
- Broadcast timer (count UP or DOWN).
- Carrying case included.

**Cellcast Specifications**

**Metering:** Panel meter indicates audio compression, RF output, power supply DC. Flashing LEDs indicate "Antenna" (VSWR) and high "Temp" fault.  
**Dimensions:** 5.5"H x 13.5"W x 8.5"D (13.97 cm x 34.29 cm x 21.59 cm).  
**Boxed Dimensions:** 9"H x 22"W x 19"D (22.86 cm x 55.88 cm x 48.26 cm).  
**Weight:** Net 8 lbs. Shipping 26 lbs.

**CELLCAST ACCESSORIES**



Included with Cellcast purchase.

- A. Battery (part #040-009).
- B. AC to DC power adapter:  
analog (part #800-37A01)  
digital (part #800-381A).
- C. 12V battery adapter cord (part #585-129).



optional sold separately:

- D. Cellcast antenna (frequency dependent).
- E. (Not shown) yagi cable (part #586-201).

