

### YC 215 - Specifications : Technical Specifications

---

#### GENERAL SPECIFICATIONS

---

**Frequency Range:**

215-265 MHz

**Bandwidth:**

8 MHz

**VSWR Over Bandwidth:**

1.5:1

**Power Rating:**

300 W

**Input Impedance:**

50 Ohms

**Gain at Mid-Frequency:**

10 dBd

**Gain, Isotropic:**

12.15 dBi

**Polarization:**

Horizontal or Vertical

**Isolation:**

20 dB

**Radiation Pattern:**

Directional

**3dB Beamwidth, Horizontal:**

45 degrees

**3dB Beamwidth, Vertical:**

60 degrees

**Front/Back Ratio:**

20 dB

#### PHYSICAL SPECIFICATIONS

---

**Mounting Type:**

Rear extended boom

**Input Connector:**

Type "N" Female

**Input Cable Provided:**

None

**Radiator Material:**

Aluminum

**Base and Fittings Material:**

Aluminum

**Number of Bays or Elements:**

6

**Length:**

3.5 ft

**Wind Area, CaAc per TIA/EIA:**

1.2 SqFt

**Max Wind Survival:**

100 MPH

**Lightning Protection:**

Tomorrow's Radio Today

# Broadcast Electronics

## Technical Specifications

Direct Ground

**Weight:**

4 lbs

**Shipping Dimensions:**

5" x 5" x 45"

**Shipping Weight:**

5 lbs.

---

### REGULATORY

NA

---

### SPECIAL NOTES

Field replaceable elements. Includes 1/4" "V" bolts for attachment up to 1-1/2" diameter nominal pipe. Can stack two units for 3dB increase in gain. Specify freq at time of order.

